

AC 1675

Cummins
Stamford
D+ &



ISO8528

GC ;) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#(#

z) \$ z'z' D:

	"	"	"	"	Amp
400/230	1675,00	1340,00	1400,00	1120,00	2020,00

fPGDL

GC ;) &

) & z

rDFDL

% %&

GC " \$(*"

z&(

GC

Standard Specifications

z

fl

!

z

ALTERNATOR

TRANSFER SWITCH

AC 1675

Cummins
Stamford
D+' &'

Manufacturer		Cummins		
Model		KTA 50 G8		
		% \$ \$	"# "	
		% (&- "		
		0% % < DQ		
	L	50,30		
	"	159 x 159		
		14,9:1		
	fl # ı	"# "	1500	
	fl ı	L	204,00	
		L	643,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	99,00		
	' # "	1700		
	' # "	261,00		
	° C	510		
		24 V d.c.		
	Load	% \$ \$ı	'+)ı) \$ı
	# "			
		289,00	222,00	155,00

		Stamford		
		PI 734C		
	Hz	50		
	"	1550		
7cg'		0,80		
		3		
	fl ı	400/230		
	A	2237		
Temperatur		H		

		fl ı		fl ı	
	"	"	"	"	L
AC 1675	10400	5500	1950	2450	2000
		fl ı		fl ı	
	"	"	"	"	L
AK 98	15200	9000	2270	3200	1900

